



Basic geometry

| | XS | S | M | L | XL |
|---------------------------------|-----------|-----------|-----------|-----------|-----------|
| Body Height in cm | ≤ 166 | 166 - 175 | 175 - 183 | 183 - 192 | ≥ 192 |
| Seat Height in mm (a) | 618 - 763 | 648 - 843 | 673 - 868 | 703 - 898 | 733 - 928 |
| Seat Tube Length in mm (b) | 415 | 420 | 420 | 450 | 480 |
| Top Tube Length in mm (c) | 559 | 585 | 609 | 633 | 656 |
| Head Tube Length in mm (d) | 90 | 90 | 100 | 115 | 130 |
| Head Tube Angle (e) | 67° | 67° | 67° | 67° | 67° |
| Seat Tube Angle (f) | 76° | 76° | 76° | 76° | 76° |
| Chainstay Length in mm (g) | 435 | 435 | 435 | 435 | 435 |
| Wheel Base in mm (h) | 1.129 | 1.155 | 1.180 | 1.206 | 1.232 |
| Stack in mm (i) | 589 | 589 | 598 | 612 | 626 |
| Reach in mm (j) | 412 | 438 | 460 | 480 | 500 |
| Stand-over Height in mm (k) | 768 | 768 | 772 | 777 | 783 |
| Bottom Bracket Offset in mm (l) | 38 | 38 | 38 | 38 | 38 |

Component geometry

| | XS | S | M | L | XL |
|---|-----------|-----------|-----------|-----------|-----------|
| Spacer in mm | 0,0 | 0,0 | 0,0 | 0,0 | 0,0 |
| Stem Length in mm | 50 | 50 | 50 | 50 | 50 |
| Handlebar Width in mm | 760 | 760 | 760 | 760 | 760 |
| Crank Length in mm | 170,0 | 170,0 | 175,0 | 175,0 | 175,0 |
| Chainring Size | 34 | 34 | 34 | 34 | 34 |
| Seat Post Diameter in mm | 31,6 | 31,6 | 31,6 | 31,6 | 31,6 |
| Dropper post travel in mm | 100 | 125 | 150 | 150 | 150 |
| Seat Post Length in mm | 380 | 455 | 480 | 480 | 480 |
| Maximum Seat Post Insertion Depth in mm | 225 | 275 | 275 | 275 | 275 |
| Minimum Seat Post Insertion Depth in mm | 80 | 80 | 80 | 80 | 80 |
| Wheel Size | 29" | 29" | 29" | 29" | 29" |
| Disc Size in mm | 180 / 160 | 180 / 160 | 180 / 160 | 180 / 160 | 180 / 160 |
| Front Fork Travel in mm | 120 | 120 | 120 | 120 | 120 |
| Rear Suspension Travel in mm | 115 | 115 | 115 | 115 | 115 |
| Fitting Length in mm | 210X50 | 210X50 | 210X50 | 210X50 | 210X50 |